

Water Based 1K Exterior Wood Coating

Sheenlac Water based PU exterior wood finish is an 1K PU clear designed to provide excellent protection for all types of outdoor wood projects from UV rays, weathering, temperature changes and humidity.

PRODUCT BENEFITS

1. Available in 30 and 60 gloss levels.
2. Durable UV protection for Wood
3. Protection from temperature changes and humidity



PRODUCT FEATURES

AVAILABLE PACK SIZES



500 ml



1 L

*Actual coverage may vary due to factors such as method and condition of application, surface roughness and porosity and weather conditions.

RECOMMENDED USE

Ideal to use on outdoor furniture, doors, window panels, fences, floors, stairs, railing, trim and wall panelling.

* Not to be applied on surfaces / substrate with continues seepage or dampness

Product	Dilution in %	Drying / Recoat time	Emery grit No.
WB 1K Epoxy Impregnation clear	No further dilution	1 hr / 4 hrs	Mild sanding with #320
WB Timber Filler - to fill Nail holes, knots and minor cracks	No further dilution	1 hr	Use #220
WB Penetrative Exterior wood stain (Burma Teak, Larch Teak, Walnut & Mahogany)	If required, add water not exceed to 20%, to reduce the color depth.	30 mins / 2 hrs	Mild sanding with #320
WB Exterior 1K PU 60 gloss clear - 2 coats	30 - 40% Potable water	30 mins / 2hrs	Mild sanding with #320 to remove dust.
WB Exterior 1K PU 30 or 60 gloss clear - 1 coat	10 - 20% Potable water	30 mins	

*Recoat and drying period may vary under different conditions

**Available only for bulk orders



PROCEDURE / INSTRUCTIONS

Surface preparation:

Raw wood:

Sand with 150 grain sandpaper to make a uniform surface that is pleasant to the touch followed by a light sanding with 220 grit fine paper. Wipe out the dust.

On previously varnished surfaces in extremely poor condition:

It is recommended to remove the old varnish completely by scrap down, and then proceed as for raw wood.

Ensure the surface should be dry, free of dust, chalk, grease and wax. Remove grease and wax with Sheenlac D-13X NC Thinner. Apply Water based protective coats by Brush or Spray method.

Storage and Transportation:

Do not store or transport the containers under direct sunlight or at elevated temperatures. Store the container in an upright position in order to avoid any leakage or damage

Shelf Life:

One year from the date of manufacturing in original tightly closed containers stored away from direct sunlight and excessive heat.

Safety, health and environment information

1. Keep containers upright, tightly closed in a cool, dry, well ventilated location
2. Keep opened containers closed and tightly closed when not in use
3. Store away from heat source, direct sunlight and other flammable materials
4. Keep out of reach of children & pets. Do not store near food, drinks or animal feed
5. Do not mix with incompatible materials
6. Wear appropriate body, eye and respiratory protection equipment
7. Work in a well ventilated area. Do not breathe vapour or sprayed contents
8. Skin contact may cause irritation. In case of skin contact wash immediately with water
9. In case of eye contact, wash immediately with plenty of water and seek immediate medical attention
10. Dispose any spilled or unused paint, containers through appropriate disposal agency
11. Do not dispose spillages or unused paint in drain ,water bodies and landfill

For product related queries, feedback and quality complaints,

Please contact:

Customer care: +91 8300 03 04 04

E-mail: ccchennai@sheenlac.in

Visit us: www.sheenlac.com

Regd. Office: Sheenlac Paints Limited

Old No. 109B, New No. 124, Developed Plots, SIDCO Industrial Estate, Ambattur, Chennai - 600098. Tamil Nadu, INDIA.

All information mentioned in this data sheet are based on tests conducted in laboratory conditions. Results may vary depending upon atmospheric conditions, application methodologies and substrates. We reserve the right to alter the given data without notice.